



Nonionic Surfactants

SINOPOL 2300 Series , Polyoxyethylene C12-13 Alcohol Ether

Trade Name	Form (30°C)	Packing (kg)	Color (30°C)	pH (1% aq.)	Specific Gravity (30°C)	1% aq. Cloud Point (°C)	Moisture (%)	Hydroxyl Value (mg KOH/g)	HLB
SINOPOL 2303	Liquid	190 Drum	A-50 Max.	5.0-7.0	0.916-0.936	—	0.5 Max.	168-180	8.1
SINOPOL 2305	Liquid	190 Drum	A-50 Max.	①5.0-7.0	—	②68-74	0.5 Max.	128.0-140.0	10.6
SINOPOL 2306H	Liquid	190 Drum	A-50 Max.	5.0-7.0	—	37-41	0.5 Max.	—	11.7
SINOPOL 2307	Liquid	190 Drum	A-50 Max.	①5.0-7.0	—	49-55	0.5 Max.	106.0-114.0	12.3
SINOPOL 2307H	Liquid	190 Drum	A-50 Max.	5.0-7.0	—	60-66	0.5 Max.	—	12.7
SINOPOL 2309	Liquid	190 Drum	A-50 Max.	①5.0-7.0	—	74-80	0.5 Max.	90.0-98.0	13.4
SINOPOL 2312	Solid	200 Drum	A-50 Max. (40°C)	①5.0-7.0	—	—	0.5 Max.	75-80	14.6
SINOPOL 2340	Flake	25 PP Bag	A-80 Max. (40°C)	5.0-7.0	—	—	0.5 Max.	26-32	18.0

① 5% aq

② 10% in 25% BC

Operating Temperature :

Sinopol 2312 ~ Sinopol 2340 - become pourable liquid at about 40°C