



Nonionic Surfactants

SINOPOL 700 Series , Polyoxyethylene Styrenated Aryl Ether

Trade Name	Form (30°C)	Packing (kg)	Color (30°C)	pH (1%aq.)	Specific Gravity (30°C)	1% aq. Cloud Point (°C)	Moisture (%)	HLB
SINOPOL 707	Liquid	200 Drum	G-5 Max.	5.0-7.0	1.095-1.115	39.0-45.0	0.5 Max.	12.0
SINOPOL P-709	Liquid	200 Drum	A-250 Max.	5.0-7.0	1.100-1.120	62.0-65.0	0.5 Max.	13.2
SINOPOL 710	Liquid	200 Drum	G-3 Max.	5.0-7.0	—	73.0-78.0	0.5 Max.	13.6
SINOPOL P-714	Paste	200 Drum	G-5 Max.	5.0-7.0	1.095-1.115 (40°C)	89.0-94.0	0.5 Max.	15.0
SINOPOL 723	Solid	20 Plastic Drum	G-5 Max.	5.0-7.0	1.090-1.110 (50°C)	①65.0-70.0	0.5 Max.	16.6

① 1% solution in 5% Na₂SO₄ aqueous solution

Operating Temperature :

Sinopol P-714 - become pourable liquid at about 40°C

Sinopol 723 - become pourable liquid at about 50°C